

Product datasheet

Specifications



addressing terminal - - for AS-I cabling system - V1/V2.1

XZMC11

⚠ Discontinued on: Jun 5, 2024

⚠ Discontinued

Main

Product or component type	Addressing terminal
Range compatibility	AS-Interface cabling system
AS-i version	V1 and V2.1
Supply	Rechargeable batteries

Complementary

Charging time	14 h
Terminal use	250 read/write operations
Display type	LCD screen 13 mm
Keypad type	Membrane 4 keys
Electrical connection	Cable for XZMG1. or ASITERACC.. Infrared cable for ASITERIR1
Protection type	Overload protection Short-circuit protection
Product weight	0.55 kg

Environment

Ambient air temperature for operation	0...55 °C
Ambient air temperature for storage	-20...55 °C
IP degree of protection	IP20

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No