

Circuit breaker VT100 Standard switching capacity N Icu = 25 kA, 415/440 V AC 3-pole, system protection Thermal-magnetic trip unit, Ir = 100 A, overload prot. Ii = 1000 A, short-circuit prot. without auxiliary release without auxiliary switches FIXED mounted

number of poles		3
Short circuit		
maximum short-circuit current breaking capacity (Icu) at 400 V rated value		25 000 A
Connections		
type of electrical connection for main current circuit		screw-type terminals
Mechanical Design		
Net Weight		0.92 kg
Approvals Certificates		
Environment	General Product Approval	other

[Environmental Con-
firmations](#)



[Confirmation](#)

[Confirmation](#)



[Miscellaneous](#)

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/lowvoltage/catalogs>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VT8110-1AA03-0AA0>
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3VT8110-1AA03-0AA0>
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VT8110-1AA03-0AA0
CAx-Online-Generator
<https://www.siemens.com/cax>
Tender specifications
<https://www.siemens.com/specifications>
Characteristic curves
https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>

last modified:

11/24/2025

