

Product datasheet

Specifications



Cable entry box 100A

MGFX630C

⚠ Discontinued on: 20 Aug 2025

⚠ Discontinued

Main

Range	MGF fusegear
Product or component type	Cable box
[Ie] rated operational current	630 A
[Ue] rated operational voltage	415 V

Complementary

Poles description	3P + N
Network frequency	50/60 Hz
Network type	AC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.0 cm
Package 1 Width	41.0 cm
Package 1 Length	50.5 cm
Package 1 Weight	12.0 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins