

Product datasheet

Specifications



Handle with electronic fuse monitor, FuPacT ISFT630

LV480828

Main

Product or component type	Fuse monitor
Electrical circuit type	Electronic
Device application	Signalling
Accessory / separate part category	Electrical accessory

Complementary

Range compatibility	FuPacT FuPacT ISFT ISFT630 fuse-switch disconnectors
Control type	Handle
[Ue] rated operational voltage	400...690 V AC 50/60 Hz
[Ie] rated operational current	5 A (AC-15) at 200...240 V AC 5 A (AC-15) at 250 V AC 5 A (DC-13) at 24 V DC
Rated breaking capacity	2 kA
Power consumption in VA	3 VA
[Ith] conventional free air thermal current	5 A
[Ui] rated insulation voltage	250 V
Minimum load	10 mA 24 V
Standards	EN 61000-4-4 EN 55022 ENV 50204 EN 61000-4-6 EN 61000-4-3 EN 61000-4-2 EN 61000-4-5
Product certifications	CE
Product weight	0.2 kg

Environment

IP degree of protection	IP20
Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Height	14.0 cm
Package 1 Width	27.5 cm
Package 1 Length	33.0 cm
Package 1 Weight	1.089 kg
Unit Type of Package 2	S04
Number of Units in Package 2	3
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	3.9 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins