



Figure similar

SIPLUS PS PSU200M 10A

SIPLUS PS PSU200M 10 A based on 6EP1334-3BA10 with conformal coating, -25...+70 °C, stabilized power supply input: 120/230-500 V AC output: 24 V/10 A DC

General information	
Technical Product Detail Page	https://i.siemens.com/1P6AG1334-3BA10-7AA0
manufacturer's article number of the basic version used for SIPLUS product versions	6EP1334-3BA10
input	
type of the power supply network	1-phase and 2-phase AC
supply voltage at AC	Set by means of selector switch on the device
supply voltage 1 at AC	120 ... 230 V
supply voltage 2 at AC	230 ... 500 V
input voltage 1 at AC	85 ... 264 V
input voltage 2 at AC	176 ... 550 V
wide range input	Yes
overvoltage overload capability	1300 Vpeak, 1.3 ms
buffering time for rated value of the output current in the event of power failure minimum	25 ms
operating condition of the mains buffering	at Vin = 120/230 V, typ. 150 ms at Vin = 400 V
line frequency	50/60 Hz
line frequency	47 ... 63 Hz
input current	
• at rated input voltage 120 V	4.4 A
• at rated input voltage 230 V	2.4 A
• at rated input voltage 500 V	1.1 A
current limitation of inrush current at 25 °C maximum	35 A
I ² t value maximum	4 A ² ·s
fuse protection type	T 6.3 A (not accessible)
fuse protection type in the feeder	Recommended miniature circuit breaker at 1-phase operation: from 6 A (10 A) characteristic C (B); required at 2-phase operation: circuit breaker 2-pole connected or circuit breaker 3RV2011-1EA10 (setting 3.8 A) or 3RV2711-1ED10 (UL 489) at 230 V; 3RV2011-1DA10 (setting 3 A) or 3RV2711-1DD10 (UL 489) at 400/500 V
output	
voltage curve at output	Controlled, isolated DC voltage
output voltage at DC rated value	24 V
output voltage	
• at output 1 at DC rated value	24 V
output voltage adjustable	Yes; via potentiometer
adjustable output voltage	24 ... 28.8 V
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	

<ul style="list-style-type: none"> • on slow fluctuation of input voltage 	0.1 %
<ul style="list-style-type: none"> • on slow fluctuation of ohm loading 	0.1 %
residual ripple	
<ul style="list-style-type: none"> • maximum 	50 mV
voltage peak	
<ul style="list-style-type: none"> • maximum 	200 mV
display version for normal operation	Green LED for 24 V OK
type of signal at output	relay contact (normally open, contact rating (SELV (ES1) must be observed): 30 V DC/0.1 A
behavior of the output voltage when switching on	Overshoot of Vout approx. 3 %
response delay maximum	1 s
voltage increase time of the output voltage	
<ul style="list-style-type: none"> • typical 	50 ms
output current	
<ul style="list-style-type: none"> • rated value 	10 A
<ul style="list-style-type: none"> • rated range 	0 ... 10 A; +60 ... +70 °C: Derating 2%/K (at 120 V, 230 V) or 3.5%/K (at 400 V)
supplied active power typical	240 W
short-term overload current	
<ul style="list-style-type: none"> • at short-circuit during operation typical 	30 A
duration of overloading capability for excess current	
<ul style="list-style-type: none"> • at short-circuit during operation 	25 ms
constant overload current	
<ul style="list-style-type: none"> • on short-circuiting during the start-up typical 	12 A
bridging of equipment	Yes; switchable characteristic
number of parallel-switched equipment resources for increasing the power	2
efficiency	
efficiency in percent	91 %
power loss [W]	
<ul style="list-style-type: none"> • at rated output voltage for rated value of the output current typical 	24 W
<ul style="list-style-type: none"> • during no-load operation maximum 	6 W
closed-loop control	
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	0.1 %
relative control precision of the output voltage load step of resistive load 50/100/50 % typical	3 %
setting time	
<ul style="list-style-type: none"> • load step 50 to 100% typical 	2 ms
<ul style="list-style-type: none"> • load step 100 to 50% typical 	2 ms
setting time	
<ul style="list-style-type: none"> • maximum 	5 ms
protection and monitoring	
design of the overvoltage protection	< 35 V
property of the output short-circuit proof	Yes
design of short-circuit protection	Alternatively, constant current characteristic approx. 12 A or latching shutdown
<ul style="list-style-type: none"> • typical 	12 A
enduring short circuit current RMS value	
<ul style="list-style-type: none"> • typical 	12 A
display version for overload and short circuit	LED yellow for "overload", LED red for "latching shutdown"
safety	
galvanic isolation between input and output	Yes
galvanic isolation	Output voltage: SELV, ES1 (IEC 62368-1), DVC As (IEC 61204-7)
operating resource protection class	Class I
leakage current	
<ul style="list-style-type: none"> • maximum 	3.5 mA
<ul style="list-style-type: none"> • typical 	0.32 mA
protection class IP	IP20
EMC	
standard	

<ul style="list-style-type: none"> • for emitted interference • for mains harmonics limitation • for interference immunity 	EN 55022 Class B EN 61000-3-2 EN 61000-6-2
standards, specifications, approvals	
certificate of suitability	
<ul style="list-style-type: none"> • CE marking • UKCA marking • Regulatory Compliance Mark (RCM) 	Yes Yes Yes
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> • in horizontal mounting position during operation • during transport • during storage 	-25 ... +70 °C; with natural convection -40 ... +85 °C -40 ... +85 °C
installation altitude at height above sea level maximum	6 000 m
ambient condition relating to ambient temperature - air pressure - installation altitude	In case of operation at altitudes of 2000 - 6000 m above sea level: Output power derating of -7.5 %/1000 m or reduction of the ambient temperature by 5 K/1000 m
relative humidity with condensation according to IEC 60068-2-38 maximum	100 %; RH incl. condensation/frost (no commissioning if condensation is present), horizontal installation
chemical resistance to commercially available cooling lubricants	Yes; incl. diesel and oil droplets in the air
resistance to biologically active substances conformity according to EN 60721-3-3	Yes; Class 3B2 mold, fungal, sponge spores (except fauna); class 3B3 upon request
resistance to chemically active substances conformity according to EN 60721-3-3	Yes; Class 3C4 (RH < 75%) incl. salt spray acc. to EN 60068-2-52 (severity level 3)
resistance to mechanically active substances conformity according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust
resistance to biologically active substances conformity according to EN 60721-3-6	Yes; Class 6B2 mold, fungal, sponge spores (except fauna)
resistance to chemically active substances conformity according to EN 60721-3-6	Yes; Class 6C3 (RH < 75%) incl. salt spray acc. to EN 60068-2-52 (severity level 3)
resistance to mechanically active substances conformity according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust
coating for equipped printed circuit board according to EN 61086	Yes; Class 2 for high availability
type of coating protection against pollution according to EN 60664-3	Yes; Type 1 protection
type of test of the coating according to MIL-I-46058C	Yes; Discoloration of the coating during service life possible
product conformity of the coating Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal Coating, Class A
connection method	
type of electrical connection	screw terminal
<ul style="list-style-type: none"> • at input • at output • for auxiliary contacts 	L, N, PE: 1 screw terminal each for 0.2 ... 2.5 mm ² single-core/finely stranded +, -: 2 screw terminals each for 0.2 ... 2.5 mm ² 13, 14 (alarm signal): 1 screw terminal each for 0.14 ... 1.5 mm ²
mechanical data	
width × height × depth of the enclosure	70 × 125 × 121 mm
installation width × mounting height	70 mm × 225 mm
required spacing	
<ul style="list-style-type: none"> • top • bottom • left • right 	50 mm 50 mm 0 mm 0 mm
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
<ul style="list-style-type: none"> • DIN-rail mounting • S7 rail mounting • wall mounting 	Yes No No
housing can be lined up	Yes
net weight	0.8 kg
accessories	
electrical accessories	Buffer module
further information internet links	

internet link	<ul style="list-style-type: none"> to website: Industry Mall https://mall.industry.siemens.com to website: Industry Online Support https://support.industry.siemens.com
additional information	
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert . (V4.7)

Classifications

	Version	Classification
eClass	14	27-04-07-01
eClass	12	27-04-07-01
eClass	9.1	27-04-07-01
eClass	9	27-04-07-01
eClass	8	27-04-90-02
eClass	7.1	27-04-90-02
eClass	6	27-04-90-02
ETIM	10	EC002540
ETIM	9	EC002540
ETIM	8	EC002540
ETIM	7	EC002540
IDEA	4	4130
UNSPSC	15	39-12-10-04

Approvals Certificates

General Product Approval

[Manufacturer Declaration](#)



[China RoHS](#)



General Product Approval

EMV

[China RoHS](#)



last modified:

5/5/2026