



Figure similar

line commutating reactor for rectifier; phases: 1; Un1(V): 400; I_{thmax} 1(A) / F1(Hz): 18 / 50; I_{LN} (A): 16.2; UK(%): 4; LN(MH): 2.69; temperature rise/insulation class: 40 /B; IP00; connection: screw/flat-type connection; EN 61558-2-20 >reactor<

| General technical data | | |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|--------------------------------------|
| product designation | | Kommut.-Drossel f. Stromrichter |
| phase number | | 1 |
| type of voltage | | AC |
| operating voltage rated value | V | 400 |
| operating frequency rated value | Hz | 50 |
| <ul style="list-style-type: none"> • — operational current at AC rated value — current at AC maximum • current at DC rated value | A | 16.2 |
| | A | 18 |
| | A | 22 |
| inductivity rated value | H | 0.0027 |
| relative inductive drop in voltage for rated value of the current, voltage and frequency | % | 4 |
| power loss [W] of the coil | W | 18 |
| power loss [W] of the iron core | W | 19.7 |
| Mechanical data | | |
| type of electrical connection for main current circuit | | screw-type terminals / tab terminals |
| width | m | 0.097 |
| height | m | 0.111 |
| depth | m | 0.115 |
| Ambient conditions | | |
| thermal class according to IEC 60085 | | B |
| ambient temperature rated value | °C | 40 |
| protection class IP | | IP00 |
| Certificates/ approvals | | |
| General Product Approval | other | |



[Confirmation](#)



Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4EM5005-6CB00>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=4EM5005-6CB00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/4EM5005-6CB00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=4EM5005-6CB00&lang=en

last modified:

4/8/2025 