

Product datasheet

Specifications



Auxiliary changeover contact 1NO + 1NC standard - for Fupact ISFT160

49883

⚠ Discontinued on: 22 Jan 2021

⚠ Discontinued

Main

Range of product	ISFT160
Range	FuPact
Device short name	auxiliary contact
Product or component type	Auxiliary contact
Device application	Connection
Range compatibility	FuPact FuPacT ISFT fuse-switch disconnecter
Auxiliary contacts type	Standard
Signal contacts composition	1 C/O
[Ith] conventional free air thermal current	2 A

Complementary

output contact breaking capacity	AC-12: 2 A at 110 V AC AC-12: 2 A at 220/240 V AC AC-12: 2 A at 250 V AC AC-12: 2 A at 48 V AC AC-15: 2 A at 110 V AC AC-15: 2 A at 220/240 V AC AC-15: 2 A at 250 V AC AC-15: 2 A at 48 V AC
Minimum load	3 mA at 24 V

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1 cm
Package 1 Width	10 cm
Package 1 Length	14 cm
Package 1 Weight	2 g

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

EU RoHS Directive

[Compliant](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

