

# Product datasheet

Specifications



## enclosed switch disconnecter, SafePacT, 160A, 3P+N

MGE1603XS

⚠ Discontinued on: 11 Nov 2022

⚠ Discontinued

### Main

Range	SafePacT 2
Product or component type	Enclosed switch-disconnector
Poles description	3P + N
[In] rated current	160 A at 40 °C
[Ue] rated operational voltage	415 V AC 50/60 Hz
Suitability for isolation	Yes
Utilisation category	AC-23
Contact position indicator	Yes
Control type	Toggle

### Complementary

Earth-leakage protection	Without
Enclosure material	Steel epoxy-polyester powder cream
Mechanical durability	40000 cycles
Electrical durability	40000 cycles In/2 20000 cycles In

### Environment

IP degree of protection	IP42 conforming to IEC 60529
-------------------------	------------------------------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.5 cm
Package 1 Width	25.5 cm
Package 1 Length	44.5 cm
Package 1 Weight	9.38 kg

### Contractual warranty

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins