

Product data sheet

Specifications



ASCO 3024 Load Bank

ASCOLBLV3024

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Resistive load bank

Complementary

Voltage Rating
380 V AC 50 Hz
400 V AC 50 Hz
415 V AC 50 Hz
440 V AC 60 Hz
480 V AC 60 Hz

Capacity Rating
220 kW
235 kW
240 kW

Load Step Resolution 1 kW

Cooling System Rating 2282355.3 Gal/hr(US) (8639.5 m3/h)

Provided Equipment
1 gland plate
Fuse
Cooling fans

Enclosure Material Zintec

Surface Finish Zinc plated

Color Gray

Connection Terminals Terminals inside)

Length 52.0 in (1320 mm)

Width 31.5 in (800 mm)

Height 49.2 in (1250 mm)

Product Weight 617.3 lb(US) (280 kg)

Environment

Ambient Air Temperature 95 °F (35 °C)

Standards
ISO 9001
CE

IP Protection
IP2X
IP54

Packing Units

Unit Type of Package 1 PCE

Nbr. of units in pkg. 1

Package 1 Height 52.0 in (132.0 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Width	31.5 in (80.0 cm)
Package 1 Length	49.2 in (125.0 cm)
Package weight(Lbs)	617.3 lb(US) (280.0 kg)

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

Use Longer



Lifetime extension

Repair **No**