

Product data sheet

Specifications



Auxiliary contacts, TeSys GS, 1 NC, early break, for GS1 32 A with direct front handle

GS2AM101

⚠ Discontinued

Main

Range of Product	TeSys
Device short name	GS2AM
Product or Component Type	Auxiliary contact
Contact application	O, I and test position signalling
Contacts type and composition	1 NC
Contact operation	Early-break
[I _{th}] conventional free air thermal current	16 A (at 104 °F (40 °C))
[I _e] rated operational current	3 A 240 V AC-15 6 A 120 V AC-15 1.5 A 480 V AC-15 1.8 A 400 V AC-15 2.8 A 24 V DC-13 0.15 A 400 V DC-13 0.27 A 250 V DC-13 0.55 A 125 V DC-13 1.4 A 48 V DC-13

Complementary

Mechanical durability	5000000 cycles
Electrical durability	1000000 cycles AC-15
Product Compatibility	GS2
switch rated current	50 A 1250 A 160 A 200 A 100 A 32 A 60 A 630 A 400 A 63 A 800 A 125 A 315 A 600 A 250 A
Type of operating handle	External right side External frontal External left side
Net Weight	0.033 lb(US) (0.015 kg)

Ordering and shipping details

Category	22640-IEC DISCONNECT-GS1,LK3
----------	------------------------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Discount Schedule 111

Returnability No



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No