


# Product datasheet

Specifications

## Motors



AC servo motor BDH - 0.41 N.m -  
8000 rpm - untapped shaft - without  
brake - IP67

BDH0403C25A2B

EAN Code: 3389118187429

! Discontinued

## Main

|                           |                                                                                              |
|---------------------------|----------------------------------------------------------------------------------------------|
| Product or component type | AC servo motors                                                                              |
| Component name            | BDH                                                                                          |
| Continuous stall torque   | 0.41 N.m for LXM15LD13M3 3 phases<br>0.41 N.m for LXM15LD13M3 single phase                   |
| Peak stall torque         | 1.46 N.m for LXM15LD13M3 at 230 V 3 phases<br>1.46 N.m for LXM15LD13M3 at 230 V single phase |
| Nominal output power      | 300 W for LXM15LD13M3 at 230 V 3 phases<br>300 W for LXM15LD13M3 at 230 V single phase       |
| Nominal torque            | 0.36 N.m for LXM15LD13M3 at 230 V 3 phases<br>0.36 N.m for LXM15LD13M3 at 230 V single phase |
| Nominal speed             | 8000 rpm for LXM15LD13M3 at 230 V 3 phases<br>8000 rpm for LXM15LD13M3 at 230 V single phase |
| Maximum mechanical speed  | 8000 rpm                                                                                     |
| Product compatibility     | LXM15LD13M3 at 230 V 3 phases<br>LXM15LD13M3 at 230 V single phase                           |
| Shaft end                 | Untapped                                                                                     |
| IP degree of protection   | IP67                                                                                         |
| Encoder type              | 2-pole resolver                                                                              |
| Speed feedback resolution | 65536 points/turn                                                                            |
| Holding brake             | Without                                                                                      |
| Mounting support          | NEMA flange                                                                                  |
| Electrical connection     | Rotatable right-angled connectors                                                            |
| Number of poles           | 6                                                                                            |

## Complementary

|                                 |                       |
|---------------------------------|-----------------------|
| Range compatibility             | Lexium 15             |
| Maximum current Irms            | 1.04 A                |
| Torque constant                 | 0.28 N.m/A at 120 °C  |
| Back emf constant               | 17.9 V/krpm at 120 °C |
| Stator resistance               | 13.5 Ohm at 20 °C     |
| Stator inductance               | 10.3 mH at 20 °C      |
| Stator electrical time constant | 0.76 ms at 20 °C      |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                         |                  |
|-------------------------|------------------|
| Maximum radial force Fr | 23 N at 8000 rpm |
|                         | 27 N at 7000 rpm |
|                         | 30 N at 6000 rpm |
|                         | 33 N at 5000 rpm |
|                         | 37 N at 4000 rpm |
|                         | 40 N at 3000 rpm |
|                         | 43 N at 2000 rpm |
|                         | 46 N at 1000 rpm |
| Maximum axial force Fa  | 0.3 x Fr         |
| Product weight          | 0.63 kg          |



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer

| Lifetime extension |    |
|--------------------|----|
| Repair             | No |