

Product data sheet

Specifications



ASCO 5500 Load Bank

ASCOLBLV5500

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Resistive load bank

Complementary

Voltage Rating	240/480 V AC 60 Hz, 3 phase
Capacity Rating	500 kW
Load Step Resolution	5 kW
Cooling System Rating	5834899.02 Gal/hr(US) (22087.1 m3/h)
Provided Equipment	Switch 3 On-Off LED 2 on LED 1 alarm indication Multi-function meter 1
Ambient Air Temperature	-18...122 °F (-28...50 °C)
Enclosure Material	Aluminium Steel
Surface Finish	Polyester powder Gray
Terminal Connections	Quick
Width	88.0 in (2235 mm)
Length	180 in (4572 mm)
Height	82.5 in (2096 mm)
Product Weight	3000.5 lb(US) (1361 kg)

Environmental

Standards ISO 9001
NEMA

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package weight(Lbs)	3000.5 lb(US) (1361 kg)

Contractual warranty

Warranty (in months) 18

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

Use Longer



Lifetime extension

Repair **No**